



SSP6316-D50: Lamp Space Intensity Distribution

Photometric Data of Luminaire

Lamp Description					
Lamp Name:	Grille lamp panel	Lamp Des:	4PCS SLT818P440-S	Lamp Weight:	5.500Kg
Manufac:	STARCO LIGHTING	Lamp Size(cm):	123.0*60.0*7.8	Light Area(cm):	0.0*0.0
Electrical:	U:277.300V I:0.284A P:72.400W			LuminareFlux:	1*8069.39 lm

Lamp Test Data			
Lamp Flux:	8069.39 lm	Center Cd.:	4153.3 cd
Max(C, γ):	(140, 0.0)	Maximum Cd.:	4217.4 cd
BeamAngle(50%):	106.0 Deg	BeamAngle(10%):	153.0 Deg
Flux(0-90):	7946.24 lm(98.5%)	Flux(90-180):	123.1 lm(1.5%)
LuminousEfficacy:	111.46 lm/W		



C Angle Range:	0-360Deg	γ Range:	0-180Deg	Test No.:	001
C Precious:	10 Deg	γ Precious:	1 Deg	Tester:	QA Shan
Distance:	5.000 m	Date:	2017-02-21	Time:	17:17:38
Other:					

SSP6316-D50: Lamp Space Intensity Distribution

Zonal Flux Diagram

Zonal Flux Diagram:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Fzone	Ftotal	%lamp	%lum
10	3880.4	4052.8	4125.3	3983.5	3932.7	3914.4	4080.2	4025.1	0-10	388.98	388.98	4.83	4.83
20	3170.4	3444.1	3956.8	3510.5	3166.4	3458.6	3913.8	3392.3	10-20	1060.70	1449.68	17.97	17.97
30	2422.6	2701.8	3681.9	2661.7	2483.7	2576.7	3555.0	2582.9	20-30	1455.45	2905.14	36.01	36.01
40	2102.9	2010.5	3256.8	2042.3	2128.3	2000.9	3072.2	1983.8	30-40	1591.09	4496.23	55.72	55.72
50	1483.0	1533.8	2421.2	1565.7	1513.2	1561.3	2280.6	1539.1	40-50	1524.80	6021.03	74.62	74.62
60	228.8	985.8	1642.7	925.2	287.7	902.1	1482.7	880.2	50-60	1117.87	7138.90	88.47	88.47
70	31.5	230.9	868.6	178.0	81.6	175.7	766.5	183.4	60-70	523.49	7662.40	94.96	94.96
80	18.7	63.8	305.6	48.2	63.0	81.3	286.7	88.6	70-80	211.20	7873.60	97.58	97.58
90	13.3	17.6	32.3	12.9	49.5	44.3	46.4	47.8	80-90	72.64	7946.24	98.48	98.48
100	12.1	12.9	10.6	10.6	42.5	40.7	40.8	39.2	90-100	30.45	7976.69	98.86	98.86
110	11.3	12.0	9.6	10.2	36.0	37.5	33.9	33.1	100-110	25.84	8002.53	99.18	99.18
120	11.1	10.9	9.3	9.6	30.6	32.3	28.6	27.0	110-120	21.24	8023.77	99.44	99.44
130	10.3	10.1	8.5	9.1	24.6	28.3	23.2	21.7	120-130	16.51	8040.28	99.64	99.64
140	9.7	9.7	8.1	8.8	18.6	22.9	18.3	17.3	130-140	12.05	8052.33	99.79	99.79
150	9.5	9.1	8.2	8.5	14.6	18.1	14.9	13.5	140-150	8.20	8060.52	99.90	99.90
160	8.7	8.6	8.1	8.5	11.2	14.3	12.2	11.4	150-160	5.17	8065.69	99.96	99.96
170	8.3	8.8	8.8	8.7	9.6	11.2	10.5	10.0	160-170	2.81	8068.50	99.99	99.99
180	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	170-180	0.89	8069.39	100.00	100.00
DEG	LUMINOUS INTENSITY:cd									UNIT:lm			


C Angle Range:	0-360Deg	γ Range:	0-180Deg	Test No. :	001
C Precious:	10 Deg	γ Precious:	1 Deg	Tester:	QA Shan
Distance:	5.000 m	Date:	2017-02-21	Time:	17:17:38
Other:					

SSP6316-D50: Lamp Space Intensity Distribution

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Lamp Description					
Lamp Name:	Grille lamp panel	Lamp Des:	4PCS SLT818P440-S	Lamp Weight:	5.500Kg
Manufac:	STARCO LIGHTING	Lamp Size(cm):	123.0*60.0*7.8	Light Area(cm):	0.0*0.0
Electrical:	U:277.300V I:0.284A P:72.400W			LuminareFlux:	1*8069.39 lm

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.06	1.03	1.00	1.04	1.01	.98	.99	.97	.94	.95	.93	.91	.92	.90	.88	.86
2.0	.95	.89	.84	.93	.87	.83	.89	.85	.81	.86	.82	.79	.83	.80	.77	.75
3.0	.85	.78	.72	.83	.77	.71	.80	.74	.70	.77	.72	.69	.75	.71	.67	.65
4.0	.76	.68	.63	.75	.68	.62	.72	.66	.61	.70	.64	.60	.68	.63	.59	.57
5.0	.69	.61	.55	.68	.60	.55	.66	.59	.54	.63	.58	.53	.62	.57	.52	.51
6.0	.63	.55	.49	.62	.54	.48	.60	.53	.48	.58	.52	.47	.56	.51	.47	.45
7.0	.57	.49	.44	.56	.49	.43	.55	.48	.43	.53	.47	.43	.52	.46	.42	.40
8.0	.53	.45	.39	.52	.44	.39	.50	.44	.39	.49	.43	.39	.48	.42	.38	.36
9.0	.49	.41	.36	.48	.41	.36	.47	.40	.35	.46	.39	.35	.44	.39	.35	.33
10.0	.45	.38	.33	.44	.37	.33	.43	.37	.32	.42	.36	.32	.41	.36	.32	.30



C Angle Range: 0-360Deg γ Range: 0-180Deg Test No.: 001
 C Precious: 10 Deg γ Precious: 1 Deg Tester: QA Shan
 Distance: 5.000 m Date: 2017-02-21 Time: 17:17:38
 Other:



SSP6316-D50: Lamp Space Intensity Distribution

WEC AND CCEC

Lamp Description					
Lamp Name:	Grille lamp panel	Lamp Des:	4PCS SLT818P440-S	Lamp Weight:	5.500Kg
Manufac:	STARCO LIGHTING	Lamp Size(cm):	123.0*60.0*7.8	Light Area(cm):	0.0*0.0
Electrical:	U:277.300V I:0.284A P:72.400W			LuminareFlux:	1*8069.39 lm

p _{cc}	80%			70%			50%			30%			10%			0
p _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
p _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.257	.146	.046	.249	.142	.045	.235	.135	.043	.223	.128	.041	.211	.122	.039	
2.0	.247	.135	.041	.240	.132	.041	.228	.127	.039	.217	.122	.038	.207	.117	.037	
3.0	.233	.124	.037	.227	.122	.037	.217	.117	.036	.207	.113	.035	.198	.109	.034	
4.0	.219	.114	.033	.214	.112	.033	.204	.108	.032	.196	.105	.032	.187	.102	.031	
5.0	.205	.105	.030	.201	.103	.030	.192	.100	.029	.184	.097	.029	.177	.095	.028	
6.0	.193	.097	.028	.189	.095	.027	.181	.093	.027	.174	.090	.027	.168	.088	.026	
7.0	.181	.090	.025	.177	.088	.025	.171	.086	.025	.164	.084	.025	.159	.082	.024	
8.0	.171	.083	.023	.167	.082	.023	.161	.081	.023	.156	.079	.023	.150	.077	.022	
9.0	.161	.078	.022	.158	.077	.022	.153	.075	.021	.147	.074	.021	.143	.072	.021	
10.0	.152	.073	.020	.150	.072	.020	.145	.071	.020	.140	.070	.020	.136	.068	.020	


ρ _{cc}	80%			70%			50%			30%			10%			0
ρ _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.202	.202	.202	.173	.173	.173	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.188	.168	.150	.161	.144	.129	.110	.099	.089	.063	.058	.052	.020	.019	.017	
2.0	.178	.144	.115	.152	.124	.100	.104	.086	.069	.060	.050	.041	.019	.016	.013	
3.0	.169	.126	.091	.145	.109	.079	.100	.075	.056	.058	.044	.033	.018	.014	.011	
4.0	.161	.112	.075	.138	.097	.065	.095	.068	.046	.055	.040	.027	.018	.013	.009	
5.0	.154	.102	.063	.132	.088	.055	.091	.061	.039	.053	.036	.023	.017	.012	.008	
6.0	.147	.093	.054	.126	.081	.047	.087	.056	.033	.051	.033	.020	.016	.011	.007	
7.0	.141	.086	.048	.121	.075	.042	.084	.052	.029	.049	.031	.018	.016	.010	.006	
8.0	.135	.080	.043	.116	.070	.037	.080	.049	.026	.047	.029	.016	.015	.009	.005	
9.0	.129	.075	.039	.111	.065	.034	.077	.046	.024	.045	.027	.014	.015	.009	.005	
10.0	.124	.071	.036	.107	.062	.031	.074	.043	.022	.043	.026	.013	.014	.008	.004	

C Angle Range: 0-360Deg γ Range: 0-180Deg Test No.: 001
 C Precious: 10 Deg γ Precious: 1 Deg Tester: QA Shan
 Distance: 5.000 m Date: 2017-02-21 Time: 17:17:38
 Other:

SSP6316-D50: Lamp Space Intensity Distribution

ISOLUX Diagram

Lamp Description					
Lamp Name:	Grille lamp panel	Lamp Des:	4PCS SLT818P440-S	Lamp Weight:	5.500Kg
Manufac:	STARCO LIGHTING	Lamp Size(cm):	123.0*60.0*7.8	Light Area(cm):	0.0*0.0
Electrical:	U:277.300V I:0.284A P:72.400W			LuminareFlux:	1*8069.39 lm




3.0% 1.2460lx 0.1158fc	5.0% 2.0766lx 0.1929fc	10.0% 4.1533lx 0.3858fc
30.0% 12.4601lx 1.1575fc	40.0% 16.6131lx 1.5434fc	50.0% 20.7661lx 1.9292fc
60.0% 24.9201lx 2.3150fc	70.0% 29.0731lx 2.7009fc	80.0% 33.2261lx 3.0867fc
90.0% 37.3791lx 3.4726fc		

C Angle Range:	0-360Deg	γ Range:	0-180Deg	Test No. :	001
C Precious:	10 Deg	γ Precious:	1 Deg	Tester:	QA Shan
Distance:	5.000 m	Date:	2017-02-21	Time:	17:17:38
Other:					

SSP6316-D50: Lamp Space Intensity Distribution

ISOCANDELA Diagram

Lamp Description					
Lamp Name:	Grille lamp panel	Lamp Des:	4PCS SLT818P440-S	Lamp Weight:	5.500Kg
Manufac:	STARCO LIGHTING	Lamp Size(cm):	123.0*60.0*7.8	Light Area(cm):	0.0*0.0
Electrical:	U:277.300V I:0.284A P:72.400W			LuminareFlux:	1*8069.39 lm




C Angle Range:	0-360Deg	γ Range:	0-180Deg	Test No.:	001
C Precious:	10 Deg	γ Precious:	1 Deg	Tester:	QA Shan
Distance:	5.000 m	Date:	2017-02-21	Time:	17:17:38
Other:					

SSP6316-D50: Lamp Space Intensity Distribution

Effective Average Illuminance Diagram

Lamp Description					
Lamp Name:	Grille lamp panel	Lamp Des:	4PCS SLT818P440-S	Lamp Weight:	5.500Kg
Manufac:	STARCO LIGHTING	Lamp Size(cm):	123.0*60.0*7.8	Light Area(cm):	0.0*0.0
Electrical:	U:277.300V I:0.284A P:72.400W			LuminareFlux:	1*8069.39 lm



Note: The Curve indicate the illuminated area and the average illumination when the luminaire is at different distance.


C Angle Range:	0-360Deg	γ Range:	0-180Deg	Test No.:	001
C Precious:	10 Deg	γ Precious:	1 Deg	Tester:	QA Shan
Distance:	5.000 m	Date:	2017-02-21	Time:	17:17:38
Other:					

SSP6316-D50: Lamp Space Intensity Distribution

Luminance Limitation Curves

Lamp Description					
Lamp Name:	Grille lamp panel	Lamp Des:	4PCS SLT818P440-S	Lamp Weight:	5.500Kg
Manufac:	STARCO LIGHTING	Lamp Size(cm):	123.0*60.0*7.8	Light Area(cm):	0.0*0.0
Electrical:	U:277.300V I:0.284A P:72.400W			LuminareFlux:	1*8069.39 lm

GLARE	CLASS	ILLUMINANCE (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300
		a	b	c	d	e	f	g	h



C/Gama	85	80	75	70	65	60	55	50	45	Unit
C0	1561	1871	2364	3146	4080	22879	81915	148303	189768	cd/m2
C90	15298	30560	54906	86858	123736	164273	204896	242116	281025	

C Angle Range: 0-360Deg γ Range: 0-180Deg Test No.: 001
 C Precious: 10 Deg γ Precious: 1 Deg Tester: QA Shan
 Distance: 5.000 m Date: 2017-02-21 Time: 17:17:38
 Other:



SSP6316-D50: Lamp Space Intensity Distribution Tester

UTILIZATION FACTORS TABLE

Lamp Description					
Lamp Name:	Grille lamp panel	Lamp Des:	4PCS SLT818P440-S	Lamp Weight:	5.500Kg
Manufac:	STARCO LIGHTING	Lamp Size(cm):	123.0*60.0*7.8	Light Area(cm):	0.0*0.0
Electrical:	U:277.300V I:0.284A P:72.400W			LuminareFlux:	1*8069.39 lm

REFLECTANCE									
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
ROOM INDEX	UTILIZATION FACTORS (PERFECT) $k(RI) \times RCR = 5$								
$k = 0.60$	64	53	46	63	53	46	61	52	46
0.80	74	64	57	73	63	57	71	62	56
1.00	83	73	66	81	72	66	79	71	65
1.25	89	80	74	88	79	74	85	78	72
1.50	94	86	79	92	84	79	89	82	78
2.00	100	93	87	98	91	86	94	89	84
2.50	103	97	91	101	95	90	97	92	88
3.00	106	100	95	103	98	94	99	95	92
4.00	109	104	100	106	102	99	102	98	96
5.00	111	107	103	108	105	102	103	101	98
ROOM INDEX	UF(total)								
According to BS EN 13032-2004			Suspended				SHRNOM=1.25		

C Angle Range: 0-360Deg γ Range: 0-180Deg Test No.: 001
 C Precious: 10 Deg γ Precious: 1 Deg Tester: QA Shan
 Distance: 5.000 m Date: 2017-02-21 Time: 17:17:38
 Other: